

AMENDMENTS TO THE CLAIMS

1. (Currently amended) Adjustable overflow for insertion into a tub-like container, comprising:
 - a foot member having a base with a discharge aperture and a cylindrical tube portion with an axial passageway communicating with said discharge aperture ;
 - wherein a tubular adjusting member is rotatably mounted on or in said tube portion, said tube portion being provided with a first adjustment opening and said adjusting member being provided with ~~a second~~ two or more additional adjustment openings, said additional adjustment openings being arranged so as to be staggered in the circumferential and axial directions, said additional adjustment openings being arranged such that, in ~~a first different~~ turning positions of said adjusting member relative to the tube portion, said first and at least one of said additional ~~second~~ adjustment openings overlap at least partially ~~and define a (first) to define different~~ overflow levels, ~~and that, in a second turning position of said adjusting member, said first and the second adjustment openings~~ or do not overlap and close the overflow.
2. (Previously presented) The overflow as claimed in claim 1, wherein the tube portion and the adjusting member are open at an end facing away from the base, thereby defining a maximum overflow level.
3. (Currently amended) The overflow as claimed in claim 1, wherein the additional adjustment openings are substantially rectangular, a lower edge in each case facing the base and defining an overflow level.
4. (Previously presented) The overflow as claimed in claim 1, wherein the tube portion has a first adjustment opening running

in the axial direction and extending from the base to an end of said tube portion distal from said base.

5. (Canceled)
6. (Previously presented) The overflow as claimed in claim 1, wherein stop means are provided for locking different relative turning positions between the adjusting member and the base.
7. (Previously presented) The overflow as claimed in claim 1, wherein the base has a flat bearing surface adjacent to the tube portion and running radially.
8. (Previously presented) The overflow as claimed in claim 1, wherein the base has two stops to limit a turning angle.
9. (Previously presented) The overflow as claimed in claim 1, wherein the discharge aperture is aligned transversely to the cylindrical tube portion.
10. (Currently amended) The overflow as claimed in claim 1, wherein the overflow consists entirely or partially of a material; ~~especially a ceramic material~~, which automatically becomes water-permeable after it has been wet for a certain time.
11. (Currently amended) The overflow as claimed in claim 1, wherein a further discharge aperture is provided, which is arranged so as to be staggered in the circumferential direction and ~~in particular~~ is disposed opposite the discharge aperture.
12. (Previously presented) The overflow as claimed in claim 1, wherein an inspection opening is disposed in the region of the base in an extension of the passageway and communicating therewith.

13. (Previously presented) The overflow as claimed in claim 12, wherein the inspection opening is sealed with a removable cap.
14. (Currently amended) The overflow as claimed in claim 1, wherein the base is provided, in the region of the passageway, with a means for connecting a drainage hose, ~~especially with an external and/or internal threaded portion, a hose union or a hose plug in member.~~
15. (Previously presented) The overflow as claimed in claim 1, wherein at least one adjustment opening and/or the open end of the adjusting member is/are designed in the form of a grating.
16. (Currently amended) A storage platform for storing, watering and transporting plants, the storage platform comprising:
 - a tub-like in design and having at least one overflow having a foot member having a base with a discharge aperture and a cylindrical tube portion with an axial passageway communicating with said discharge aperture ;
 - wherein a tubular adjusting member is rotatably mounted on or in said tube portion, said tube portion being provided with a first adjustment opening and said adjusting member being provided with ~~a second~~ two or more additional adjustment openings, said additional adjustment openings being arranged so as to be staggered in the circumferential and axial directions, said additional adjustment openings being arranged such that, in ~~a first~~ different turning positions of said adjusting member relative to the tube portion, said first and ~~second~~ at least one of said additional adjustment openings overlap at least partially ~~and define a (first)~~ to define different overflow levels, ~~and that, in a second turning position of said adjusting member, said first and the second adjustment openings~~ or do not overlap[[,]] and close the overflow, the overflow for defining a desired level of liquid.

17. (Previously presented) The storage platform as claimed in claim 16, wherein the storage platform is rectangular and has two mounting members in each case on two parallel narrow sides for hanging them in rack struts, each mounting member having an engagement end portion ending freely.
18. (Previously presented) The storage platform as claimed in claim 17, wherein the engagement end portions of the mounting members are in each case disposed in a corner region of the storage platform.
19. (Currently amended) The storage platform as claimed in claim 16, wherein an outlet member is disposed on the storage platform, ~~which is made in particular of ceramic material~~ and automatically becomes water-permeable after it has been wet for a certain time.
20. (Currently amended) A watering device for storing, watering and transporting plants, comprising:
 - at least two storage platforms arranged one on top of the other, the platforms having a tub-like design and having at least one overflow having a foot member having a base with a discharge aperture and a cylindrical tube portion with an axial passageway communicating with said discharge aperture ;
 - a tubular adjusting member rotatably mounted on or in said tube portion, said tube portion being provided with a first adjustment opening and said adjusting member being provided with ~~a second~~ two or more additional adjustment openings, said additional adjustment openings being arranged so as to be staggered in the circumferential and axial directions, said adjustment openings being arranged such that, in ~~a first~~ different turning positions of said adjusting member relative to the tube portion, said first and ~~second~~ at least one of said additional adjustment openings overlap at least partially and

~~define a (first) to define different overflow levels, and that, in a second turning position of said adjusting member, said first and the second adjustment openings~~ or do not overlap[[,]] and close the overflow, the overflow;

wherein said storage platforms being arranged in such a way that any liquid draining away via the overflow of a/each storage platform flows into a storage platform below, ~~especially~~ and/or one arranged immediately adjacent to it.

21. (New) The overflow as claimed in claim 1, wherein each of the additional adjustment openings is smaller than the first adjustment opening.